



## Reel Amusements, L.L.C.

1522 Sarah Court  
Murfreesboro, TN 37129  
1-800-624-3779  
Fax: (615) 895-9184  
[www.ReelGaming.com](http://www.ReelGaming.com)

Friday, June 10, 2011

### **Removing CRT Monitor and Replacing with LCD in Sitdown Cabinets**

- Unplug power cord from the wall
- Open Bill compartment door and remove existing bezel
- Remove back door
- Unplug 3 pin connector from monitor for power
- Unplug video cable and users control board
- Remove 4 bolts holding CRT monitors down from the back of cabinet
- Lift monitor out of cabinet from the front

To install the LCD monitor, first the brackets need to be adjusted. There are two brackets on either side of monitor, remove screws, move brackets toward the front of monitor as far as it will go, and then replace screws.

- Mount the LCD monitor to bezel, making sure clear plexi seats between the brackets. Large side of bezel will be at the bottom of the cabinet.
- Plug the power brick to LCD monitor and other end to power source.
- Plug video cable (included) to the LCD Monitor making sure the red wire is just under the "R". Plug the other end of cable to the existing video cable in the game, matching red to red/white; blue to blue/white, etc.
- Install LCD monitor with bracket into game where old bezel was taken from. Close the bill acceptor door and also top making sure the bezel fits into the groove.